

## ilepo 2025 120W Multiple Charger 3C+3A i90



### Hot Selling Point

- With support for AC 100 - 240V/50 - 60Hz input voltage, this charger is not afraid of voltage differences in any region of the world. Whether in Europe and the United States with diverse voltage standards or other overseas regions with complex power environments, it can easily connect to the local power supply, stabilize the power supply, and ensure a smooth charging process.
- The powerful total power of 120W makes the charging efficiency far superior to ordinary chargers. When charging multiple devices at the same time, it can also maintain an extremely fast state, greatly shorten the charging time, quickly charge the device to full power, and help you quickly return to the rhythm of work and entertainment.
- Equipped with 3 USB-C ports and 3 USB-A ports. Among them, USB-C1 and C2 ports support 5V/3A - 20V/3.25A output, with advanced PPS function (3.3 - 11V/5A, 3.3 - 21V/3A, 65W Max), and the power distribution is 45W + 20W when two ports are used simultaneously. The USB - C3 port can provide 5V/3A - 20V/1.5A output, with a maximum power of 30W. The 3 USB - A ports (QC3.0) all support 5V/3A - 5V4.5A output, with a maximum power of 22.5W, C3 + A1 combined output 12W + 12W, A2 + A3 combined output 25W. With such a rich port configuration, almost all electronic devices on the market can be adapted, meeting the charging needs of the whole family in one stop.
- Equipped with PD3.0 and PPS cutting-edge technologies, the charging process is both efficient and safe. Intelligently identify the power required by the device, accurately supply power, avoid hidden dangers such as overcharging and overheating, and protect the device battery in all directions to extend the service life of the device.

## Specifications

Model No.	i90	
General	Input	AC 100-240V/50-60Hz
	Output	USB-C1/USB-C2:5V/3A,9V/3A,12V/3A,15V/3A,20V/3.25A PPS: 3.3-11V/5A、3.3-21V/3A 65W(Max) USB-C1+USB-C2 : 45W+20W USB-C3:5V/3A,9V/3A,12V/2.5A,15V/2A,20V/1.5A30W(Max) USB-A1QC3.0:5V/3A,9V/2A,12V/1.5A,4.5V5A,5V4.5A22.5W(Max) USB-C3+USB-A1:12W+12W USB-A2 QC3.0 : 5V/3A,9V/2A,12V/1.5A、4.5V5A,5V4.5A 22.5W(Max) USB-A3 QC3.0 : 5V/3A,9V/2A,12V/1.5A,4.5V5A,5V4.5A 22.5W(Max) USB-A2+USB-A3 :25W
	Interface	USB-C
	Color	Black/White
	Outer box color	Color box
Package	Unit Size	80*40*105mm
	N.W	218 g
	Package size	216*16*18mm
	Carton size	47.5*45.2*15.3cm
	Quantity	40pcs/carton
	G.W	16kg/carton

